

| | |
|--|--|
| Construction Material | Stainless Steel |
| Installation Type | Hardwired |
| Volts | See Technical Specifications Chart |
| Watts | See Technical Specifications Chart |
| Control Screen Size | 7" |
| Maximum Adjusted Cubic Feet | See Technical Specifications Chart |
| Kilowatt Rating (kW) | See Technical Specifications Chart |
| Minimum Time | 15 MIN |
| Maximum Time | 60 MIN |
| AMPS | See Technical Specifications Chart |
| Water Supply Connection | 3/8" NPT Water Inlet & 1/2" NPT Steam Outlet |
| Wire Gauge | See Technical Specifications Chart |
| Generator Pipe Fitting & Tubing | 3/8" NPT & 1/2" NPT |
| Drain Connection | 1/2" NPT |
| Generator Phase | 1 PH |
| Generator Max Temperature | 113°F (45°C) |
| Generator Line Fuse | See Technical Specifications Chart |
| Generator Fuel Type & Power | Electric |
| Control Dimensions | 12.38"L x 8.88"W x 6.38"H |
| SteamHead Dimensions | 3"L x 3"W x 1.5"H |
| AutoFlush Dimensions | 4.25"L x 5"W x 2.75"H |
| MS Series Generator Dimensions | 21"L x 11"W x 16" |
| MS Series Package Shipping Dimensions | 24"L x 18"W x 24"H |
| MS Series Package Weight | 41 lbs |
| Super Series Generator Dimensions | 21"L x 11"W x 16" |
| Super Series Package Shipping Dimensions | 23"L x 24"W x 22"H |
| Super Series Package Weight | 54 lbs |